


Indoor Lighting



Key Features

- IP40 suitable for indoor environments
- Impact rating of IK08
- Efficacy of up to 141lm/W
- Nominal life-time of > 72,000 h (L80/B10)
- Colour stability with 3 step MacAdam
- High colour rendering index CRI > 80
- Emergency BLF = 445 lm

Part No.

W

L

Lm/W

L

Part No.	W	L	Lm/W	L
IM/11/1997/4	14	1997	141	1170
IM/11/2645/4	19	2645	139	1170
IM/11/3255/4	24	3255	135	1170
IM/14/3225/4	23	3225	135	1450
IM/14/4347/4	33	4347	131	1450
IM/14/5496/4	42	5496	129	1450

Options

- For Microprismatic /MP
- For Opal /OP
- For Surface/Suspended suffix /S
- For Recessed suffix /R
- For Black suffix /BLK
- For White suffix /WHI
- For DALI Dimable suffix /DIM
- For Self-Contained 3hr emergency suffix /EMR
- For 3hr Self-test emergency suffix /ST
- For DALI EM-PRO 3hr emergency suffix /EMP

i.e. **IM/14/5496/4/S/B/DIM/** =
Imogen 1450mm, Suspended Black Luminaire, 5496lm, 42w, 4k, DALI Dimmable c/w DALI EM-PRO 3hr emergency

For more information, please contact Sales@ldl.lighting

Accessories

- 2m Wire Suspension **IM/WSK**

