



Indoor Lighting





Key Features

- Efficacy of up to 161lm/W
- Nominal life-time of 100,000 hours L80/B10
- Colour stability with 3 step MacAdam
- Body and gear tray - aluminium extrusion
- Opal frosted diffuser - polycarbonate TP(a)
- Optics - PMMA TP(b)
- Modular optics - shade polycarbonate, optic - PMMA
- Colours: RAL 9003 White, RAL 9005 Black & RAL 9006 Grey
- IP20 as Standard, IP44 available on request
- Lengths available: 570mm 850mm 1130mm 1410mm 1690mm 1970mm 2250mm 2530mm 2810mm 3090mm 3370mm.

Fitting Lengths (mm)



Indoor Lighting



Direct only						
Part No.	Lm	W	Lm/W	BLF	Weight	L (mm)
MIL/S/11/OP/1307/4	1307	9	140	413	2.6kg	1130
MIL/S/11/OP/2616/4	2616	19	137	413	2.6kg	1130
MIL/S/11/OP/3836/4	3836	29	132	413	2.6kg	1130
MIL/S/16/OP/1961/4	1961	14	136	416	3.8kg	1690
MIL/S/16/OP/3925/4	3925	28	137	416	3.8kg	1690
MIL/S/16/OP/5753/4	5753	43	132	416	3.8kg	1690
MIL/S/22/OP/2614/4	2614	18	140	417	5.2kg	2250
MIL/S/22/OP/5232/4	5232	38	137	417	5.2kg	2250
MIL/S/22/OP/7671/4	7671	58	132	417	5.2kg	2250

Other lengths and outputs are available on request.


Options

- 4000K supplied as standard /4
 - For 3000K suffix /3
 - For white RAL 9003 finish suffix /WHI
 - For black RAL 9005 finish suffix /BLK
 - For grey RAL 9006 finish suffix /GRY
 - For DALI dimmable system suffix /DIM
 - For Casambi enabled system suffix /CAS
 - For wireless DALI suffix /WD
 - For 3hr integral emergency suffix /EMR
 - For 3hr self-test emergency suffix /ST
 - For DALI addressable emergency suffix /EMP
 - For wireless DALI addressable emergency /WAE
- i.e.: Millie, Suspended/Surface,1690mm, opal diffuser, 3925 lumens, 28W, 4000K, black RAL 9005 finish c/w 3 hr emergency = MIL/S/16/OP/3925/4/BLK/EMR

Accessories

- Suspended / Surface end cap MIL/ECS
- Wire suspension kit (2m) MIL/WIRE
- Wall mounting bracket MIL/WALL
- Coupler MIL/CPLR

Indoor Lighting



Direct only						
Part No.	Lm	W	Lm/W	Weight	L (mm)	
MIL/S/11/MP/1272/4	1272	9	136	2.6kg	1130	
MIL/S/11/MP/2546/4	2546	19	133	2.6kg	1130	
MIL/S/11/MP/3732/4	3732	29	128	2.6kg	1130	
MIL/S/16/MP/1908/4	1908	14	132	3.8kg	1690	
MIL/S/16/MP/3819/4	3819	28	133	3.8kg	1690	
MIL/S/16/MP/5598/4	5598	43	128	3.8kg	1690	
MIL/S/22/MP/2544/4	2544	18	136	5.2kg	2250	
MIL/S/22/MP/5091/4	5091	38	133	5.2kg	2250	
MIL/S/22/MP/7464/4	7464	58	128	5.2kg	2250	

Options

- 4000K supplied as standard
- For 3000K suffix
- For white RAL 9003 finish suffix
- For black RAL 9005 finish suffix
- For grey RAL 9006 finish suffix
- For DALI dimmable system suffix
- For Casambi enabled system suffix
- For wireless DALI suffix
- For 3hr integral emergency suffix
- For 3hr self-test emergency suffix
- For DALI addressable emergency suffix
- For wireless DALI addressable emergency

- /4
- /3
- /WHI
- /BLK
- /GRY
- /DIM
- /CAS
- /WD
- /EMR
- /ST
- /EMP
- /WAE

Other lengths and outputs are available on request.



Accessories

- Suspended / Surface end cap
- Wire suspension kit (2m)
- Wall mounting bracket
- Coupler

- MIL/ECS
- MIL/WIRE
- MIL/WALL
- MIL/CPLR

- i.e.: Millie, Suspended/Surface, 1690mm, microprism diffuser, 3750 lumens, 30W, 4000K, black RAL 9005 finish c/w 3 hr emergency = MIL/S/16/MP/3750/4/BLK/EMR

Indoor Lighting



Direct only

Part No.	Lm	W	Lm/W	BLF	Weight	L (mm)
MIL/S/11/90/1020/4	1021	8	121	427	2.8kg	1130
MIL/S/11/90/2010/4	2007	14	146	427	2.8kg	1130
MIL/S/11/90/2980/4	2975	20	152	427	2.8kg	1130
MIL/S/16/90/1550/4	1553	11	139	430	4.1kg	1690
MIL/S/16/90/3060/4	3056	19	159	430	4.1kg	1690
MIL/S/16/90/4520/4	4520	28	161	430	4.1kg	1690
MIL/S/22/90/2070/4	2071	14	140	431	5.6kg	2250
MIL/S/22/90/4010/4	4014	24	141	431	5.6kg	2250
MIL/S/22/90/5950/4	5950	40	141	431	5.6kg	2250

Other lengths and outputs are available on request.

Options



- 4000K supplied as standard /4
- For 3000K suffix /3
- For white RAL 9003 finish suffix /WHI
- For black RAL 9005 finish suffix /BLK
- For grey RAL 9006 finish suffix /GRY
- For DALI dimmable system suffix /DIM
- For Casambi enabled system suffix /CAS
- For wireless DALI suffix /WD
- For 3hr integral emergency suffix /EMR
- For 3hr self-test emergency suffix /ST
- For DALI addressable emergency suffix /EMP
- For wireless DALI addressable emergency /WAE

Accessories

- Suspended / Surface end cap MIL/ECS
- Wire suspension kit (2m) MIL/WIRE
- Wall mounting bracket MIL/WALL
- Coupler MIL/CPLR

- i.e.: Millie, Suspended/Surface, 1130mm, 90° optic, 2007 lumens, 14W, 4000K, black RAL 9005 finish, Casambi enabled = MIL/S/11/90/2010/4/BLK/CAS

Indoor Lighting



Direct only					
Part No.	Lm	W	Lm/W	Weight	L (mm)
MIL/S/11/AS/1420/4	1424	11	132	2.8kg	1130
MIL/S/11/AS/2160/4	2156	15	142	2.8kg	1130
MIL/S/11/AS/2830/4	2827	20	142	2.8kg	1130
MIL/S/16/AS/2140/4	2145	15	144	4.1kg	1690
MIL/S/16/AS/3260/4	3260	22	151	4.1kg	1690
MIL/S/16/AS/4410/4	4411	29	154	4.1kg	1690
MIL/S/22/AS/2850/4	2848	19	150	5.6kg	2250
MIL/S/22/AS/4310/4	4312	28	155	5.6kg	2250
MIL/S/22/AS/5650/4	5654	37	153	5.6kg	2250

Other lengths and outputs are available on request.

Options

- 4000K supplied as standard /4
- For 3000K suffix /3
- For white RAL 9003 finish suffix /WHI
- For black RAL 9005 finish suffix /BLK
- For grey RAL 9006 finish suffix /GRY
- For DALI dimmable system suffix /DIM
- For Casambi enabled system suffix /CAS
- For wireless DALI suffix /WD
- For 3hr integral emergency suffix /EMR
- For 3hr self-test emergency suffix /ST
- For DALI addressable emergency suffix /EMP
- For wireless DALI addressable emergency /WAE



Accessories

- Suspended / Surface end cap
- Wire suspension kit (2m)
- Wall mounting bracket
- Coupler

MIL/ECS
MIL/WIRE
MIL/WALL
MIL/CPLR

- i.e.: Millie, Suspended/Surface, 1130mm, asymmetric optic, 2827 lumens, 20W, 4000K, grey RAL 9006 finish, DALI dimmable = **MIL/S/11/AS/2830/4/GRY/DIM**

Indoor Lighting



Direct only

Part No.	Lm	W	Lm/W	Weight	L (mm)
MIL/S/11/DA/1390/4	1386	11	128	2.8kg	1130
MIL/S/11/DA/2070/4	2069	15	136	2.8kg	1130
MIL/S/11/DA/2740/4	2744	20	138	2.8kg	1130
MIL/S/16/DA/2200/4	2200	15	148	4.1kg	1690
MIL/S/16/DA/3280/4	3282	22	152	4.1kg	1690
MIL/S/16/DA/4340/4	4343	29	152	4.1kg	1690
MIL/S/22/DA/2770/4	2772	19	146	5.6kg	2250
MIL/S/22/DA/4140/4	4138	28	149	5.6kg	2250
MIL/S/22/DA/5490/4	5488	37	148	5.6kg	2250

Other lengths and outputs are available on request.

Options

- 4000K supplied as standard /4
- For 3000K suffix /3
- For white RAL 9003 finish suffix /WHI
- For black RAL 9005 finish suffix /BLK
- For grey RAL 9006 finish suffix /GRY
- For DALI dimmable system suffix /DIM
- For Casambi enabled system suffix /CAS
- For wireless DALI suffix /WD
- For 3hr integral emergency suffix /EMR
- For 3hr self-test emergency suffix /ST
- For DALI addressable emergency suffix /EMP
- For wireless DALI addressable emergency /WAE

Accessories

- Suspended / Surface end cap MIL/ECS
- Wire suspension kit (2m) MIL/WIRE
- Wall mounting bracket MIL/WALL
- Coupler MIL/CPLR

- i.e.: Millie, Suspended/Surface, 1130mm, double asymmetric optic, 2744 lumens, 20W, 4000K, grey RAL 9006 finish, DALI dimmable = **MIL/S/11/DA/2740/4/GRY/DIM**