


Lily 4

Downlighter

Innovation.
Collaboration.
Illumination.



Indoor Lighting



Key features

- IP20 suitable for internal environments
- Impact rating of IK04
- Efficacy of up to 91 m/W
- Nominal life-time of > 50,000 h (L70/B50)
- Colour stability with 3 step MacAdam
- Very high colour rendering index CRI > 90
- Emergency BLF = 254 lm

Options

- For White bezel option suffix **/W**
- For Black bezel option suffix **/B**
- For 24° suffix **/24D**
- For 36° suffix **/36D**
- For Dali dimmable option (DC only) suffix **/DIM**

* GU10 available as 36° only

i.e. **LIL/4/DC13/2/B/36D/DIM =**

Lily Adjustable Downlight, 1140lm, 13w, 2700K, Black finish
36°, Dali Dimmable

Part No.	Watt	Lm	CRi	CCT	H (mm)
LIL/4/AC10/2	10	710	90	2700	80
LIL/4/AC10/3	10	760	90	3000	80
LIL/4/AC10/4	10	810	90	4000	80
LIL/4/DC10/2	10	770	90	2700	65
LIL/4/DC10/3	10	840	90	3000	65
LIL/4/DC10/4	10	890	90	4000	65
LIL/4/DC13/2	13	1140	90	2700	75
LIL/4/DC13/3	13	1170	90	3000	75
LIL/4/DC13/4	13	1270	90	4000	75
LIL/4/GU10*	5	355	80	2700	85

For more information, please contact Sales@ldl.lighting