

Crookes Downlighter





- Efficacies up to 103lm/W
- Impact rating of IK04
- IP44 suitable for internal environments
- Nominal life-time of 50,000h (L70/B10)
- High colour rendering index CRI > 80
- Emergency BLF = 314lm


To Specify:

Select Part Number with additional options if required e.g. **CRO/2/1400/4/DIM**

= Crookes downlight, 14W, 1435lm, 4000K, DALI dimmable



luminaire	cutout
L x H, mm	mm
Ø113x55	Ø90 – 100
Ø143x59	Ø117 – 127
Ø200x68	Ø168 – 178



Part No.	W	lm	lm/W	CCT
CRO/1/1000/3	10	1000	100	3000K
CRO/1/1000/4	10	1025	103	4000K
CRO/2/1400/3	14	1400	100	3000K
CRO/2/1400/4	14	1435	103	4000K
CRO/3/2000/3	20	2000	100	3000K
CRO/3/2000/4	20	2050	103	4000K

Options

For DALI dimmable suffix

For Casambi enabled suffix

For leading/trailing edge dimmable suffix

For 3hr emergency suffix

For self-test emergency suffix

For DALI addressable emergency suffix

/DIM
/CAS
/MDIM
/EMR
/ST
/EMP

