


Dominique M Surface



- IP20 suitable for internal environments
- Impact rating of IK05
- Efficacy of up to 127lm/W
- Nominal life-time of 100,000 h (L80/B10)
- Colour stability with 3 step MacAdam
- CRI 80 as standard, CRI 90 available on request



To Specify:

Select Part Number with additional options if required

e.g. **DOM/M/1357/4/60D/DIM/EMR**

= Dominique Medium, 11W, 1357 lumens, 4000K, 60D, DALI dimmable c/ w 3hr self-contained emergency

Part No. (3000K)	Lm	W	lm/W
DOM/M/1281/20D/3	1281	11	120
DOM/M/2775/20D/3	2775	26	105
DOM/M/1271/40D/3	1271	11	119
DOM/M/2754/40D/3	2754	26	105
DOM/M/1289/60D/3	1289	11	121
DOM/M/2792/60D/3	2792	26	106

Part No. (4000K)	Lm	W	lm/W
DOM/M/1349/20D/4	1349	11	127
DOM/M/2921/20D/4	2921	26	111
DOM/M/1338/40D/4	1338	11	126
DOM/M/2899/40D/4	2899	26	110
DOM/M/1357/60D/4	1357	11	127
DOM/M/2939/60D/4	2939	26	112


Options

For black finish suffix
 For white finish suffix
 For DALI dimmable suffix
 For 3hr emergency suffix
 For DALI addressable emergency suffix
 For self test suffix


/BLK
 /WHI
 /DIM
 /EMR
 /EMP
 /ST

Dominique Surface

20° Optic:



40° Optic:



60° Optic:

