
## **Eden** Trunking System






### To Specify:

Select Part Number with additional options if required e.g. **EDEN/TS/3000/7** 

= Eden Trunking System 3000mm with 7 pole through wiring

Part No.	Length
EDEN/TS/1500	1500mm
EDEN/TS/3000	3000mm
EDEN/TS/4500	4500mm



#### Accessories

For 1m suspension electric cable

For 1m suspension kit

For 800mm chain suspenion kit

For T grid profile 15mm ceiling bracket

For T grid profile 24mm ceiling bracket

For ceiling bracket

EDEN/SUSP/I/EC EDEN/SUSP/I EDEN/SUSP/CH/800 EDEN/BRK/T15 EDEN/BRK/T24 EDEN/BRK





Three-phase operation: Ideal for large buildings, this option enables long, uninterrupted lines and individual luminaire control for optimal energy savings. Two-phase operation + emergency lighting: This configuration utilizes the spare conductor for emergency lighting, offering versatility for various applications.





Three-phase operation + Lighting Management System (LMS): This option leverages the additional conductors for dimmable electronic gears and continuous connection in long lines, with basic switching control.

Two-phase operation + emergency lighting + LMS: This configuration combines emergency lighting with the ability to integrate dimmable control gears.

#### 11 Pole



The pinnacle of flexibility, this option offers unlimited possibilities beyond basic power, emergency lighting, and LMS. It allows for the seamless sequential integration of various systems, including sensors, control devices, additional lighting circuits, motion sensors, and even low-voltage power supplies for LMS components.



# **Eden** Trunking System









