

Henry Downlighter



- Efficacies up to 130lm/W
- Impact rating of IK02
- IP20 suitable for internal environments
- Nominal life-time of 50,000h (L90/B10)
- Colour stability with 3 step MacAdam
- High colour rendering index CRI > 80
- Emergency BLF = 360lm

To Specify:

Select Part Number with additional options if required
e.g. **HEN/1500/4/DIM/EMR**

= Henry, 1541 lumens, 13W, 4000K, DALI dimmable c/w 3hr emergency

Part No.	W	lm	lm/W	H(mm)	CCT
HEN/1100/3	10	1080	111	110	3000K
HEN/1100/4	10	1117	114	110	4000K
HEN/1500/3	13	1487	112	110	3000K
HEN/1500/4	13	1541	114	110	4000K
HEN/2300/3	18	2298	127	125	3000K
HEN/2300/4	18	2390	130	125	4000K
HEN/2700/3	22	2675	122	125	3000K
HEN/2800/4	22	2819	126	125	4000K
HEN/3200/3	27	3154	121	125	3000K
HEN/3200/4	27	3269	123	125	4000K

Options

For DALI dimmable suffix	/DIM
For Casambi enabled suffix	/CAS
For tunable white suffix	/TW
For 3hr emergency suffix	/EMR
For self-test emergency suffix	/ST
For DALI addressable emergency suffix	/EMP
For wireless dimmable system suffix	/WD
For wireless addressable emergency suffix	/WAE

