

Henry MSU Downlighter



- MSU certified
- Efficacies up to 126lm/W
- Impact rating of IK10
- IP44 suitable for internal environments
- Nominal life-time of 50,000h (L90/B10)
- Colour stability with 3 step MacAdam
- High colour rendering index CRI > 80
- Emergency BLF = 315lm

To Specify:

Select Part Number with additional options if required

e.g. **HEN/MSU/2200/4/DIM/EMR**

= Henry MSU, 2270 lumens, 18W, 4000K, DALI dimmable c/w 3hr emergency

Part No.	W	lm	lm/W	H(mm)	CCT
HEN/MSU/1000/3	10	1026	102	110	3000K
HEN/MSU/1000/4	10	1061	106	110	4000K
HEN/MSU/1400/3	13	1412	108	110	3000K
HEN/MSU/1400/4	13	1463	112	110	4000K
HEN/MSU/2200/3	18	2183	121	125	3000K
HEN/MSU/2200/4	18	2270	126	125	4000K
HEN/MSU/2600/3	22	2541	115	125	3000K
HEN/MSU/2600/4	22	2678	121	125	4000K
HEN/MSU/3000/3	27	2996	110	125	3000K
HEN/MSU/3000/4	27	3105	115	125	4000K

Options

For DALI dimmable suffix

/DIM

For Casambi enabled suffix

/CAS

For tunable white suffix

/TW

For 3hr emergency suffix

/EMR

For self-test emergency suffix

/ST

For DALI addressable emergency suffix

/EMP

For wireless addressable emergency suffix

/WAE

