

LED3 Kit Emergency Downlight




- Plug and Play with Plugs and Sockets
- Extra Long Life LiFePO4 Batteries
- High output of 267lm
- 1000mA Emergency Output
- Non-Maintained Operation
- Cables with Strain Relief for Simple Installation

To Specify:

Select Part Number with additional options if required
e.g. **LED3/KIT/W/OA/IP/ST**

= LED3 Kit, white, open area optic, IP54, 3hr self-test emergency



Part No.	Lm	W	Halo	IP rating	Battery
LED3/KIT	267	2	Non-dim	IP54	LiFePO4
LED3/KIT/DIM	267	2	Dimming	IP20	LiFePO4

Options

For white (Ral 9016) finish suffix
For black (Ral 9005) finish suffix
For open Area optic suffix
For corridor optic suffix
For self-test emergency suffix
For DALI emergency suffix
For wireless addressable emergency suffix
For IP54 Rating

/W
/B
/OA
/CO
/ST
/EMP
/WAE
/IP


Open Area Spacing Table

Mounting Height	To Wall		Between Fittings	
	0.5 Lux	1.0 Lux	0.5 Lux	1.0 Lux
2.5m	5.4m	4.5m	12.5m	10.7m
3.0m	5.9m	4.7m	13.9m	11.7m
4.0m	6.6m	-	16.2m	13.1m
5.0m	0.3m	-	17.7m	0.5m
6.0m	6.9m	-	18.7m	-

Corridor Spacing Table

Mounting Height	Along Corridor (length)				Along Corridor (width)			
	To Wall		Between Fittings		Between Fittings		To Wall	
	0.5 Lux	1.0 Lux	0.5 Lux	1.0 Lux	0.5 Lux	1.0 Lux	0.5 Lux	1.0 Lux
2.5m	9.9m	8.1m	22.3m	19.7m	7.9m	6.3m	3.1m	2.4m
3.0m	10.7m	8.4m	25.4m	21.5m	8.4m	6.6m	3.3m	2.4m
4.0m	11.8m	0.4m	29.5m	23.5m	9.2m	6.8m	3.4m	0.2m
5.0m	11.5m	-	32.2m	22.9m	9.6m	6.2m	3.1m	-
6.0m	-	-	33.5m	-	9.6m	-	-	-

Corridor



Open Area

