

Millie Corner Systems



- Efficacies up to 126lm/W
- Nominal life time of 100,000 (L80,B10)
- Colour stability with 3 step MacAdam
- Body and gear tray - aluminium extrusion
- Opal frosted diffuser - polycarbonate TP(a)
- Colours: RAL 9003 White, RAL 9005 Black & RAL 9006 Grey
- IP20 as Standard, IP44 available on request

To Specify:

Select Part Number with additional options if required e.g. **MIL/S/COR/OP/2500/4/BLK/EMR**

= Millie, Suspended/Surface, Corner, Opal diffuser, 2540lm, 22W, 4000K, Black RAL 9005, Emergency

Part No.	W	Lm	lm/W	Weight	L (mm)
MIL/S/COR/OP/1900/4	18	1900	106	1.14kg	600/543
MIL/S/COR/OP/2500/4	22	2540	115	1.14kg	600/543
MIL/S/COR/OP/3700/4	30	3780	126	1.14kg	600/543
MIL/S/COR/OP/5000/4	40	5000	125	1.14kg	600/543
MIL/S/COR/OP/6200/4	49	6200	124	1.14kg	600/543

Options

For 4000K optic suffix	/4
For 3000K optic suffix	/3
For white RAL 9003 finish suffix	/WHI
For black RAL 9005 finish suffix	/BLK
For grey RAL 9006 finish suffix	/GRY
For DALI dimmable suffix	/DIM
For Casambi enabled suffix	/CAS
For wireless dimmable system suffix	/WD
For 3hr emergency suffix	/EMR
For 3hr self-test emergency suffix	/ST
For 3hr DALI emergency suffix	/EMP
For wireless addressable emergency	/WAE

