



- Efficacies up to 121lm/W
- Impact rating of IK10
- IP65 Certified to European Community Directive No.2014/34/EU and ATEX approved
- Nominal life-time of 72,000h (L80/B10)
- Minimum ambient temperature -20°C
- Maximum ambient temperature  $t_a=40^{\circ}\text{C}$
- Emergency BLF = 334lm
- CRI 80 as standard, CRI 90 available on request

## To Specify:

Select Part Number with additional options if required e.g. **PRI/5/4790/EMR PRIMEX LED**  
 = ZONE II, 1500mm, 4790lm, 4K c/w 3hr emergency

| Part No.          | W  | lm   | lm/W | A(mm) | Weight |
|-------------------|----|------|------|-------|--------|
| <b>PRI/2770/4</b> | 24 | 2770 | 115  | 1272  | 3.2kg  |
| <b>PRI/3730/4</b> | 31 | 3730 | 120  | 1272  | 3.2kg  |
| <b>PRI/5200/4</b> | 43 | 5200 | 121  | 1272  | 3.4kg  |
| <b>PRI/7260/4</b> | 60 | 7260 | 121  | 1272  | 3.5kg  |
| <b>PRI/3430/5</b> | 30 | 3430 | 114  | 1572  | 4.1kg  |
| <b>PRI/4790/5</b> | 40 | 4790 | 120  | 1572  | 4.2kg  |
| <b>PRI/6490/5</b> | 54 | 6490 | 120  | 1572  | 4.3kg  |
| <b>PRI/8710/5</b> | 73 | 8710 | 119  | 1572  | 4.4kg  |

## Options

For wireless addressable emergency suffix  
 For wireless dimmable system suffix  
 For emergency suffix  
 For DALI dimmable suffix  
 For casambi enabled suffix  
 For self-test suffix  
 For DALI addressable emergency suffix

**/WAE**  
**/WD**  
**/EMR**  
**/DIM**  
**/CAS**  
**/ST**  
**/EMP**

