

Street Medium Post Top



- IP66 suitable for external environments
- Impact rating of IK08
- Efficacy of up to 146lm/W
- Nominal life-time of 102,000h (L90/B10)
- Installation Height 6-8m
- Operating Temperature from -40 to +50°
- Net Weight 5.5kg
- Spigot size—Ø 60mm

To Specify:

Select Part Number with additional options if required

e.g. **ST/M/AS2/6056/4**

= Street Medium, AS2 Lens, 6056lm, 46W, 4000K

AS1 Lens	Lm	W	lm/W	CCT
ST/M/AS1/3916/4	3916	26	146	4000K
ST/M/AS1/5477/4	5477	38	142	4000K
ST/M/AS1/6549/4	6549	46	141	4000K
ST/M/AS1/7406/4	7406	54	136	4000K

AS2 Lens	Lm	W	lm/W	CCT
ST/M/AS2/3683/4	3683	26	137	4000K
ST/M/AS2/5116/4	5116	38	133	4000K
ST/M/AS2/6056/4	6056	46	131	4000K
ST/M/AS2/6964/4	6964	54	128	4000K

AREA Lens	Lm	W	lm/W	CCT
ST/M/AREA/4797/4	4797	26	179	4000K
ST/M/AREA/6662/4	6662	38	173	4000K
ST/M/AREA/7917/4	7917	46	171	4000K
ST/M/AREA/9119/4	9119	54	167	4000K

