


Dominique 95 Surface



- IP20 suitable for internal environments
- Impact rating of IK05
- Efficacy of up to 110lm/W
- Nominal life-time of 90,000 h (L80/B10)
- Colour stability with 3 step MacAdam
- CRI 80 as standard, CRI 90 available on request
- Dimmable and Emergency control gear remote



To Specify:

Select Part Number with additional options if required

e.g. **DOM/S/1263/4/60D/DIM**

= Dominique S surface downlighter, 11W, 1263lm, 4000K, 60D, DALI dimmable

Part No. (3000K)	Lm	W	lm/W
DOM/95/1160/20D/3	1160	11	101
DOM/95/1758/20D/3	1758	20	88
DOM/95/1183/40D/3	1183	11	103
DOM/95/1756/40D/3	1756	20	88
DOM/S/1200/60D/3	1200	11	105
DOM/S/1780/60D/3	1780	20	89

Part No. (4000K)	Lm	W	lm/W
DOM/95/1221/20D/4	1221	11	107
DOM/95/1851/20D/4	1851	20	92
DOM/95/1246/40D/4	1246	11	109
DOM/95/1848/40D/4	1848	20	92
DOM/95/1263/60D/4	1263	11	110
DOM/95/1874/60D/4	1874	20	94


Options

For black finish suffix
 For white finish suffix
 For DALI dimmable suffix
 For 3hr emergency suffix
 For DALI addressable emergency suffix
 For self test suffix


/BLK
 /WHI
 /DIM
 /EMR
 /EMP
 /ST

Dominique Surface

20° Optic:



40° Optic:



60° Optic:

