

Alexa Surface



- IP40 suitable for internal environments
- Impact rating of IK08
- Efficacy of up to 159lm/W
- Nominal life-time of 100,000h (L80/B10)
- Colour stability with 3 step MacAdam
- High colour rendering index CRI > 80
- Emergency BLF = 445lm

To Specify:

Select Part Number with additional options if required
e.g. **ALEX/5/3478/4/DIM/EMR**

= Alexa LED surface luminaire, 3478lm, 23W, 4000K, Dali Dimmable
c/w 3hr emergency.

Part No.	W	lm	lm/W	Length
ALEX/4/1339/4	9	1339	144	1200
ALEX/4/2672/4	19	2672	140	1200
ALEX/4/4006/4	29	4006	138	1200
ALEX/4/5124/4	39	5124	130	1200
ALEX/4/6343/4	49	6343	127	1200
ALEX/5/1851/4	11	1851	159	1480
ALEX/5/3478/4	23	3478	146	1480
ALEX/5/5198/4	36	5198	143	1480
ALEX/5/6625/4	49	6625	135	1480
ALEX/5/8164/4	62	8164	131	1480

Options

For Casambi enabled suffix

For 3 hour Maintained Emergency option suffix

For DALI Dimmable suffix

For 3hr Self-test emergency suffix

For DALI 3hr emergency suffix

/CAS
/EMR
/DIM
/ST
/EMP

