

Banda Surface



- IP40 suitable for internal environments
- Impact rating of IK06
- Efficacy of up to 144lm/W
- Nominal life-time of 100,000h (L80/B10)
- Colour stability with 3 step MacAdam
- High colour rendering index CRI > 80
- Emergency BLF = 315lm

To Specify:

Select Part Number with additional options if required e.g. **BAN/5/3431/4/DIM/EMR**

= Banda 5ft batten, 3431 lumens, 4000K, Dali dimmable c/w 3hr self-contained emergency

Part No.	W	lm	lm/W	Weight
BAN/4/2084/4	14	2084	144	1.5kg
BAN/4/2745/4	19	2745	141	1.5kg
BAN/4/3392/4	24	3392	138	1.5kg
BAN/5/3431/4	26	3431	131	2kg
BAN/5/4239/4	33	4239	128	2kg
BAN/5/5810/4	47	5810	123	2kg

Fixings (mm)	W	L1	L2	L3
1200mm	1200	610	800	159.5
1500mm	1500	610	840	289.5

Options

For 3000K suffix

For 3 hour Maintained Emergency option suffix

For DALI Dimmable suffix

For 3hr Self-test emergency suffix

For DALI 3hr emergency suffix

/3
/EMR
/DIM
/ST
/EMP

