


Millie Recessed Opal System



- Body and gear tray - aluminium extrusion
- IP20 as standard, IP44 available on request
- Efficacy of up to 161lm/W
- Nominal life-time of 100,000 h (L80/B10)
- Colour stability with 3 step MacAdam
- Opal frosted diffuser - polycarbonate TP(a)
- Optics - PMMA TP(b)
- Modular optics - shade polycarbonate, optic - PMMA
- Colours: RAL 9003 White, RAL 9005 Black & RAL 9006 Grey
- Lengths available: 570mm, 850mm, 1130mm, 1410mm, 1690mm, 1970mm, 2250mm, 2530mm, 2810mm, 3090mm, 3370mm

To Specify:


Select Part Number with additional options if required
 e.g. **MIL/R/16/OP/3925/4/BLK/DIM**
 = Millie, Recessed, 1690mm, Opal, 3925lm, 28W, 4000K, Black RAL 9005 finish, DALI dimmable



Part No.	Lm	W	Lm/W	BLF	Weight	L (mm)
MIL/R/11/OP/1307/4	1307	9	140	413	2.6kg	1130
MIL/R/11/OP/2616/4	2616	19	137	413	2.6kg	1130
MIL/R/11/OP/3836/4	3836	29	132	413	2.6kg	1130
MIL/R/16/OP/1961/4	1961	14	136	416	3.8kg	1690
MIL/R/16/OP/3925/4	3925	28	137	416	3.8kg	1690
MIL/R/16/OP/5753/4	5753	43	132	416	3.8kg	1690
MIL/R/22/OP/2614/4	2614	18	140	417	5.2kg	2250
MIL/R/22/OP/5232/4	5232	38	137	417	5.2kg	2250
MIL/R/22/OP/7671/4	7671	58	132	417	5.2kg	2250

Options


- For 4000K suffix /4
- For 3000K suffix /3
- For white finish suffix /WHI
- For black finish suffix /BLK
- For grey finish suffix /GRY
- For Casambi enabled suffix /CAS
- For DALI Dimmable suffix /DIM
- For wireless DALI suffix /WD
- For 3hr integral emergency suffix /EMR
- For 3hr self-test emergency suffix /ST
- For DALI addressable emergency suffix /EMP
- For wireless DALI addressable emergency /WAE
- For 90° low glare optic /90
- For Asymmetric wall wash optic /AS
- For Double asymmetric optic /DA
- Integral Sensor /SEN



Accessories

- Recessed end cap /MIL/ECR
- Recessing bracket /MIL/R/BRKT
- Coupler /MIL/CPLR


Fitting Lengths (mm)



Millie Recessed Microprismatic System



- Body and gear tray - aluminium extrusion
- IP20 as standard, IP44 available on request
- Efficacy of up to 161lm/W
- Nominal life-time of 100,000 h (L80/B10)
- Colour stability with 3 step MacAdam
- Opal frosted diffuser - polycarbonate TP(a)
- Optics - PMMA TP(b)
- Modular optics - shade polycarbonate, optic - PMMA
- Colours: RAL 9003 White, RAL 9005 Black & RAL 9006 Grey
- Lengths available: 570mm, 850mm, 1130mm, 1410mm, 1690mm, 1970mm, 2250mm, 2530mm, 2810mm, 3090mm, 3370mm



To Specify:

Select Part Number with additional options if required


e.g. **MIL/R/22/MP/2544/4/BLK/DIM**

= Millie, Recessed, 2250mm, Microprismatic, 2544lm, 18W, 4000K, Black RAL 9005 finish, DALI dimmable

Part No.	Lm	W	Lm/W	Weight	L (mm)
MIL/R/11/MP/1272/4	1272	9	136	2.6kg	1130
MIL/R/11/MP/2546/4	2546	19	133	2.6kg	1130
MIL/R/11/MP/3732/4	3732	29	128	2.6kg	1130
MIL/R/16/MP/1908/4	1908	14	132	3.8kg	1690
MIL/R/16/MP/3819/4	3819	28	133	3.8kg	1690
MIL/R/16/MP/5598/4	5598	43	128	3.8kg	1690
MIL/R/22/MP/2544/4	2544	18	136	5.2kg	2250
MIL/R/22/MP/5091/4	5091	38	133	5.2kg	2250
MIL/R/22/MP/7464/4	7464	58	128	5.2kg	2250

Options

- For 4000K suffix /4
- For 3000K suffix /3
- For white finish suffix /WHI
- For black finish suffix /BLK
- For grey finish suffix /GRY
- For Casambi enabled suffix /CAS
- For DALI Dimmable suffix /DIM
- For wireless DALI suffix /WD
- For 3hr integral emergency suffix /EMR
- For 3hr self-test emergency suffix /ST
- For DALI addressable emergency suffix /EMP
- For wireless DALI addressable emergency suffix /WAE
- For 90° low glare optic /90
- For Asymmetric wall wash optic /AS
- For Double asymmetric optic /DA
- Integral Sensor /SEN



Accessories

- Recessed end cap /MIL/ECR
- Recessing bracket /MIL/R/BRKT
- Coupler /MIL/CPLR

Fitting Lengths (mm)

