



- Efficacies up to 121lm/W
- Impact rating of IK10
- IP65 Certified to European Community Directive No.2014/34/EU and ATEX approved
- Nominal life-time of 72,000h (L80/B10)
- Minimum ambient temperature -20°C
- Maximum ambient temperature $t_a=40^{\circ}\text{C}$
- Emergency BLF = 334lm
- CRI 80 as standard, CRI 90 available on request

To Specify:

Select Part Number with additional options if required e.g. **PRI/5/4790/EMR PRIMEX LED**
 = ZONE II, 1500mm, 4790lm, 4K c/w 3hr emergency

Part No.	W	lm	lm/W	A(mm)	Weight
PRI/2770/4	24	2770	115	1272	3.2kg
PRI/3730/4	31	3730	120	1272	3.2kg
PRI/5200/4	43	5200	121	1272	3.4kg
PRI/7260/4	60	7260	121	1272	3.5kg
PRI/3430/5	30	3430	114	1572	4.1kg
PRI/4790/5	40	4790	120	1572	4.2kg
PRI/6490/5	54	6490	120	1572	4.3kg
PRI/8710/5	73	8710	119	1572	4.4kg

Options

For wireless addressable emergency suffix
 For wireless dimmable system suffix
 For emergency suffix
 For DALI dimmable suffix
 For casambi enabled suffix
 For self-test suffix
 For DALI addressable emergency suffix

/WAE
/WD
/EMR
/DIM
/CAS
/ST
/EMP

