


Samson Aluminium Base Bulkhead



- IP65 suitable for external environments
- Impact rating of IK10
- Efficacy of up to 133lm/W
- Nominal life-time of 81,000h (L80/B10)
- Colour stability with 3 step MacAdam
- High colour rendering index CRI > 80
- Emergency BLF = 358 lm
- Suitable for side conduit entry
- Black or white cast aluminium base available
- Fitted with a hinged gear tray




To Specify:

Select Part Number with additional options if required
e.g. **SAM/2820/4/S/W/F3/ST**

= Samson bulkhead, 2823 lm, 22W, 4000K, square, white c/w sensor, corridor function & self-test

Part No.	W	lm	lm/W	CCT
SAM/1800/3/S	14	1801	129	3000K
SAM/1900/4/S	14	1900	136	4000K
SAM/2550/3/S	21	2549	124	3000K
SAM/2690/4/S	21	2694	131	4000K
SAM/1210/3/S	11	1212	113	3000K
SAM/1280/4/S	11	1282	120	4000K
SAM/1720/3/S	15	1722	115	3000K
SAM/1820/4/S	15	1822	122	4000K
SAM/2320/3/S	18	2317	128	3000K
SAM/2420/4/S	18	2419	133	4000K
SAM/2700/3/S	22	2705	126	3000K
SAM/2820/4/S	22	2823	131	4000K
SAM/3070/3/S	25	3066	123	3000K
SAM/3200/4/S	25	3196	128	4000K



Options

For 3 hour Maintained Emergency option suffix

For DALI Dimmable suffix

For 3hr Self-test emergency suffix

For DALI 3hr emergency suffix

For White suffix

For Black suffix

For Microprismatic

For wireless dimmable suffix

For wireless addressable emergency suffix

/EMR

/DIM

/ST

/EMP

/W

/B

/CAS

/WD

/WAE

Sensor Options

On-off, no daylight control suffix

On-off, with daylight control suffix

Corridor function, no daylight control suffix

Corridor function, with daylight control suffix

Dimm to off, no daylight control suffix

Dimm to off, with daylight control suffix

/F1

/F2

/F3

/F4

/F5

/F6