

Street Large Post Top



- IP66 suitable for external environments
- Impact rating of IK08
- Efficacy of up to 146lm/W
- Nominal life-time of 102,000h (L90/B10)
- Installation Height 8-12m
- Operating Temperature from -40 to +50°
- Net Weight 7kg
- Spigot size—Ø 60mm

To Specify:

Select Part Number with additional options if required
e.g. **ST/L/AS2/7565/4**

= Street Large, AS2 Lens, 7565lm, 49W, 4000K

AS1 Lens	Lm	W	lm/W	CCT
ST/L/AS1/5206/4	5206	34	149	4000K
ST/L/AS1/7317/4	7317	49	147	4000K
ST/L/AS1/8599/4	8599	60	142	4000K
AS2 Lens	Lm	W	lm/W	CCT
ST/L/AS2/5049/4	5049	34	145	4000K
ST/L/AS2/7565/4	7565	49	144	4000K
ST/L/AS2/8457/4	8457	60	140	4000K
AREA Lens	Lm	W	lm/W	CCT
ST/L/AREA/6451/4	6451	34	185	4000K
ST/L/AREA/9012/4	9012	49	181	4000K
ST/L/AREA/10561/4	10561	60	175	4000K
L2 Lens	Lm	W	lm/W	CCT
ST/L/L2/6193/4	6193	34	178	4000K
ST/L/L2/8886/4	8886	49	178	4000K
ST/L/L2/10257/4	10257	60	170	4000K

