

Lola Bed Head Luminaire



- IP65 suitable for external/wet environments
- Impact rating of IK10
- Efficacy of up to 132lm/W
- Nominal life-time of 81,000h (L80/B10)
- Colour stability with 3 step MacAdam
- High colour rendering index CRI > 80
- Emergency BLF = 377 lumens

To Specify:

Select Part Number with additional options if required
 e.g. **LOL/2620/4/CAS**
 = Lola bulkhead, 21W, 2616lm, 4000K, white bezel, Casambi enabled

Part No.	W	lm	lm/W	CCT
LOL/1750/3	14	1751	125	3000K
LOL/1850/4	14	1845	132	4000K
LOL/2480/3	21	2481	120	3000K
LOL/2620/4	21	2616	127	4000K
LOL/2230/3	18	2231	123	3000K
LOL/2330/4	18	2326	128	4000K
LOL/2940/3	25	2945	118	3000K
LOL/3080/4	25	3080	123	4000K

Options

For Emergency suffix	/EMR
For DALI dimmable	/DIM
For self-test suffix	/ST
For DALI 3hr emergency suffix	/EMP
For Casambi enabled suffix	/CAS
For switch dimmable suffix	/SDIM
For wireless DALI dimmable suffix	/WD
For wireless DALI addressable emergency suffix	/WAE
For brass bezel suffix	/BR
For chrome bezel suffix	/CH
For satin silver bezel suffix	/SS

Sensor Options

On-Off, no daylight control suffix	/F1
On-off, with daylight control suffix	/F2
Corridor function, no daylight control suffix	/F3
Corridor function, with daylight control suffix	/F4
Dimm to off, no daylight control suffix	/F5
Dimm to off, with daylight control suffix	/F6

