

# Millie Corner Systems



- Efficacies up to 126lm/W
- Nominal life time of 100,000 (L80,B10)
- Colour stability with 3 step MacAdam
- Body and gear tray - aluminium extrusion
- Opal frosted diffuser - polycarbonate TP(a)
- Colours: RAL 9003 White, RAL 9005 Black & RAL 9006 Grey
- IP20 as Standard, IP44 available on request

## To Specify:

Select Part Number with additional options if required e.g. **MIL/S/COR/OP/2500/4/BLK/EMR**

= Millie, Suspended/Surface, Corner, Opal diffuser, 2540lm, 22W, 4000K, Black RAL 9005, Emergency

Part No.	W	Lm	lm/W	Weight	L (mm)
MIL/S/COR/OP/1900/4	18	1900	106	1.14kg	610/543
MIL/S/COR/OP/2500/4	22	2540	115	1.14kg	610/543
MIL/S/COR/OP/3700/4	30	3780	126	1.14kg	610/543
MIL/S/COR/OP/5000/4	40	5000	125	1.14kg	610/543
MIL/S/COR/OP/6200/4	49	6200	124	1.14kg	610/543

## Options

- For 4000K optic suffix
- For 3000K optic suffix
- For white RAL 9003 finish suffix
- For black RAL 9005 finish suffix
- For grey RAL 9006 finish suffix
- For DALI dimmable suffix
- For Casambi enabled suffix
- For wireless dimmable system suffix
- For 3hr emergency suffix
- For 3hr self-test emergency suffix
- For 3hr DALI emergency suffix
- For wireless addressable emergency
- Integral Sensor

- /4
- /3
- /WHI
- /BLK
- /GRY
- /DIM
- /CAS
- /WD
- /EMR
- /ST
- /EMP
- /WAE
- /SEN

