



- Efficacies up to 160lm/W
- Impact rating of IK08
- IP66 suitable for internal environments
- Colour stability with 3 step MacAdam
- Nominal life-time of 100,000h (L80/B10)
- Emergency BLF = 410lm
- HO Emergency BLF = 640lm
- Not suitable for wall mounted external environments

To Specify:

Select Part Number with additional options if required e.g. **WPZ/5/4841/4/EMR**

= WPZ, 1575mm, 31W, 4841lm, 4000K, 3hr emergency

Part No.	W	lm	lm/W	L(mm)	Weight
WPZ/4/2422/4	16	2422	150	1285	2.1kg
WPZ/4/3791/4	25	3791	150	1285	2.1kg
WPZ/4/5058/4	34	5058	145	1285	2.1kg
WPZ/4/6184/4	45	6184	136	1285	2.1kg
WPZ/5/3117/4	19	3117	160	1575	2.5kg
WPZ/5/4841/4	31	4841	156	1575	2.5kg
WPZ/5/6438/4	43	6438	149	1575	2.5kg
WPZ/5/8010/4	56	8010	142	1575	2.5kg

Options

For wireless addressable emergency suffix

For wireless dimmable system suffix

For emergency suffix

For DALI dimmable suffix

For casambi enabled suffix

For self-test suffix

For DALI addressable emergency suffix

For PIR sensor suffix

For microwave sensor suffix

For switch dimmable suffix

/WAE

/WD

/EMR

/DIM

/CAS

/ST

/EMP

/PIR

/MW

/SDIM

