

Leona Pendant



- IP20 suitable for internal environments
- Efficacy of up to 123lm/W
- Nominal life-time of 54,000 h (L90/B10)
- Impact rating of IK06
- High colour rendering index CRI > 90
- Suspended via ceiling rose
- Made from high quality cast aluminium
- Colour stability with 3 step MacAdam
- Available in lengths from 250mm up to 2400mm
- Custom finish colours also available

To Specify:

Select Part Number with additional options if required e.g.

LEONA/36D/861/94/W/DIM

= Leona, 36 degree optic, 861lm, 8W, 90CRI, 4000K, White, Dali dimmable

Part No.	W	lm	lm/W	D(mm)
LEONA/12D/361/94	4	361	100	ø12
LEONA/12D/755/94	8	755	99	ø24
LEONA/12D/1135/94	13	1135	89	ø35
LEONA/24D/445/94	4	445	123	ø12
LEONA/24D/861/94	8	861	113	ø24
LEONA/24D/1349/94	13	1349	106	ø35
LEONA/36D/445/94	4	445	123	ø12
LEONA/36D/861/94	8	861	113	ø24
LEONA/36D/1349/94	13	1349	106	ø35

Options

For 2700K colour temperature suffix
 For 3000K colour temperature suffix
 For 4000K colour temperature suffix
 For DALI Dimmable suffix
 For Casambi enabled suffix
 For white gear housing suffix
 For black gear housing suffix

/27
 /3
 /4
 /DIM
 /CAS
 /WHI
 /BLK

